



Anti-Corrosion, Aerospace, Architectural, Marine Coatings

Parking Lot & Driveway Coating

Technical Data

DESCRIPTION	Parking Lot & Driveway represents a dramatic improvement in the repair and coating of driveways and parking lots. It is extremely resistant to virtually all forms of environmental attack, including; rain, snow, summer heat and wear from vehicle and pedestrian traffic.
USES	Parking Lot & Driveway can be sprayed, rolled or troweled over asphalt and concrete surfaces. It will effectively protect and seal the asphalt binder from erosion and environmental damage. The asphalt binder will remain protected against environmental and vehicular traffic. NOTE: Parking Lot & Driveway when applied on sharp, protruding, and exposed aggregate will wear as vehicles drive over the surface. To effectively coat a surface with exposed aggregate, additional coats will be needed. Notice the condition of the substrate before applying to determine the suitability for every individual application.
COLOUR	Available in black or grey
COMPATIBLE SYSTEMS	Parking Lot & Driveway can be top coated with conventional latex coatings that match most architectural colours.

SHEEN	Flat	GENERIC TYPE	Water-based rubber filled acrylic
SOLVENT	Deionized or Tap Water	V.O.C. (volatile organic compound)	Less than 90g per litre
SOLIDS BY WEIGHT	± 50%	RECOMMENDED DFT	8-10 mils per sq. m / coat
SOLIDS BY VOLUME	± 50%	SPREADING RATE	6-8 sq. m / L
WEIGHT PER LITRE	1.1 kg per litre	DRY TIME @24°C 50%R.H.* (*Relative Humidity)	TACK FREE ≈ 2 hours HARD ≈ 48 hours

PERFORMANCE DATA			
TENSILE, PSI	-	701	
%ELONGATION AT MAX LOAD	-	197.1	
SALT SPRAY AFTER 500 HR	-	No blistering	
ASTM D1653, grns/hr.ft. ² - permeability	-	0.136	
ACCELERATED AGING - 2000hr UV	-	100.6%	
LOW TEMP FLEX AFTER 1000hr UV	-	No cracking	

APPLICATION	Parking Lot & Driveway should be applied when the air and surface temperature is between 7°C and 37°C. See label application details for complete application instructions.
MAINTENANCE	Touch-up and repairs are easily done with a paint brush and are also recommended if needed.
SHELF LIFE	12 Months in original unopened container when stored in a protected area where the temperature is between 5°C to 30°C.

SAFETY INFORMATION	Use with adequate ventilation. Avoid contact with eyes. Avoid prolonged breathing of vapour. Refer to Material Safety Data Sheet (MSDS). <i>NOTE: The technical data given herein has been compiled for your help and guidance and is based upon our experience and knowledge. It is subject to modification from time to time in the light of experience and our policy of continuous product development. Persons using this product must first satisfy themselves as to its suitability for the intended purpose. Please contact your sales representative for complete recommendations.</i>
---------------------------	--

